

## CentOS6

/etc/rc.d/init.d/tomcat

```
#
# tomcat Start/Stop Script for the Tomcat Server
#
# chkconfig: 2345 91 14
# description: start/stop script for tomcat server

# source function library
. /etc/rc.d/init.d/functions

export LANG=ko_KR.euckr
export JAVA_HOME=/data/apps/search/java
export TOMCAT_HOME=/data/apps/search/tomcat
export LD_LIBRARY_PATH=${LD_LIBRARY_PATH}:/usr/local/glibc-2.14
export CLASSPATH="."

PRGDIR="$TOMCAT_HOME/bin"

# Check that target executable exists
if [ ! -x "$PRGDIR"/"$EXECUTABLE" ]; then
echo "Cannot find $PRGDIR/$EXECUTABLE"
echo "This file is needed to run this program"
exit 1
fi

case "$1" in
start)
echo -n "Starting Tomcat service: "
daemon --user search "$PRGDIR"/startup.sh
iptables -t nat -A PREROUTING -p tcp --dport 80 -j REDIRECT --to-port 8080
;;
stop)
echo -n "Shutting down Tomcat service: "
daemon --user search "$PRGDIR"/shutdown.sh
;;
restart)
$0 stop
$0 start
;;
*)
echo "Usage: $0 {start|stop|restart}"
```

```
exit 1
esac
echo
exit 0
#####
```

chkconfig -add tomcat service tomcat start service tomcat stop

## CentOS7



( : ) (

2020-02-26)

## Windows

## Ref

From:

<http://125.132.25.164/dokuwiki/> -  
2023.12

Permanent link:

<http://125.132.25.164/dokuwiki/doku.php?id=was:tomcat:autostart&rev=1590138551>

Last update: **2022/03/10 19:52**

