CentOS6

/etc/rc.d/init.d/tomcat

```
#
# tomcat Start/Stop Script for the Tomcat Server
#
# chkconfig: 2345 91 14
# description: start/stop script for tomcat server

# source function library
. /etc/rc.d/init.d/functions


export LANG=ko_KR.euckr
export JAVA_HOME=/data/apps/search/java
export TOMCAT_HOME=/data/apps/search/tomcat
export LD_LIBRARY_PATH=${LD_LIBRARY_PATH}:/usr/local/glibc-2.14
export CLASSPATH="."


PRGDIR="$TOMCAT_HOME/bin"


# Check that target executable exists
if [ ! -x "$PRGDIR"/"$EXECUTABLE" ]; then
echo "Cannot find $PRGDIR/$EXECUTABLE"
echo "This file is needed to run this program"
exit 1
fi


case "$1" in
start)
echo -n "Starting Tomcat service: "
daemon --user search "$PRGDIR"/startup.sh
iptables -t nat -A PREROUTING -p tcp --dport 80 -j REDIRECT --to-port 8080
;;
stop)
echo -n "Shutting down Tomcat service: "
daemon --user search "$PRGDIR"/shutdown.sh
;;
restart)
$0 stop
$0 start
;;
*)
```

```
echo "Usage: $0 {start|stop|restart}"
exit 1
esac
echo
exit 0
#####################################################
```

```
                   user
  daemon –user search "$PRGDIR"/startup.sh
  iptable              8080    80
  iptables -t nat -A PREROUTING -p tcp –dport 80 -j REDIRECT –to-port 8080
```

```
[root@dev ~] chkconfig --add tomcat
[root@dev ~] service tomcat start
[root@dev ~] service tomcat stop
```

CentOS7 (   )

☑   (:   ) (.   2020-02-26)

/usr/lib/systemd/system/tomcat7.service

```
[Unit]

Description=tomcat7
After=network.target syslog.target


[Service]

Type=forking

#tomcat              root,                    search
User=root
Group=root


ExecStart=/opt/search/tomcat7/bin/catalina.sh start
ExecStop=/opt/search/tomcat7/bin/catalina.sh stop

#Umask, RestartSec  Restart        10
              . (    )
Umask=0022
ReStartSec=10
Restart=always
```

```
[Install]

WantedBy=multi-user.target
```

```
[root@dev ~] systemctl enable /usr/lib/systemd/system/tomcat7.service
# tomcat7.service      tomcat7
[root@dev ~] systemctl start tomcat7.service #
[root@dev ~] systemctl start tomcat7.service #
[root@dev ~] systemctl status tomcat7.service #
```

tomccat7.service   .

```
[root@dev ~] systemctl daemon-reload
#
[root@dev ~] journalctl -xe
[root@dev ~] journalctl -f #tail
```

Windows

Ref

[CentOS7 service(systemd unit)](#)

        ,