

MariaDB

- description : MariaDB, Mysql
- author :
- email : dhan@repia.com
- lastupdate : 2020-02-08

•

/

CentOS7

```
//
[mysql@dev tmp]$ systemctl status mariadb

//
[mysql@dev tmp]$ systemctl enable mariadb

// MariaDB
[mysql@dev tmp]$ systemctl restart mariadb
```

, Dump

[MariaDB](#)
[mysqldump](#)
[mysqldump](#)
[\[Project :: Server\] MariaDB](#)

mysql db

user table 가

```
INSERT INTO mysql.`user`
(Host, `User`, Password, Select_priv, Insert_priv, Update_priv, Delete_priv,
Create_priv, Drop_priv, Reload_priv, Shutdown_priv, Process_priv, File_priv,
Grant_priv, References_priv, Index_priv, Alter_priv, Show_db_priv,
Super_priv, Create_tmp_table_priv, Lock_tables_priv, Execute_priv,
```

```

Repl_slave_priv, Repl_client_priv, Create_view_priv, Show_view_priv,
Create_routine_priv, Alter_routine_priv, Create_user_priv, Event_priv,
Trigger_priv, Create_tablespace_priv, ssl_type, ssl_cipher, x509_issuer,
x509_subject, max_questions, max_updates, max_connections,
max_user_connections, plugin, authentication_string, password_expired,
is_role)
VALUES('%', '__user__', password('__password__'), 'Y', 'Y', 'Y', 'Y', 'Y',
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',
'', 'N', 'N')
;

```

db table 가

```

INSERT INTO mysql.db
(Host, Db, `User`, Select_priv, Insert_priv, Update_priv, Delete_priv,
Create_priv, Drop_priv, Grant_priv, References_priv, Index_priv, Alter_priv,
Create_tmp_table_priv, Lock_tables_priv, Create_view_priv, Show_view_priv,
Create_routine_priv, Alter_routine_priv, Execute_priv, Event_priv,
Trigger_priv)
VALUES('%', '__db__', '__user__', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'N', 'Y',
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y');

```

```

FLUSH privileges;

```

```

MariaDB [(none)]> create user '${User }'@'${Host }' identified by
'${Password }';
Query OK, 0 rows affected (0.00 sec)

```

(\${DB })

```

MariaDB [(none)]> grant all privileges on ${DB }.* to '${User }'@'${Host }';
Query OK, 0 rows affected (0.00 sec)

```

```

MariaDB [(none)]> flush privileges;
Query OK, 0 rows affected (0.00 sec)

```

LOCK, UNLOCK

```

ALTER USER '${User }'@'${Host }' ACCOUNT LOCK;
ALTER USER '${User }'@'${Host }' ACCOUNT UNLOCK;

```

MySQL, MariaDB DB, , 가
[mysql] mysql, mariaDB , 가
Account Locking

(function)

```
[
mysql> SHOW PROCEDURE STATUS

[
mysql> SHOW CREATE PROCEDURE uso_Get_Mini_Evaluation

[
mysql> SHOW CREATE VIEW v_core_ability_examination
```

MySQL ,

- ID,CD NAME
- delimiter() (X)

```
delimiter $$
DROP FUNCTION IF EXISTS dbname.getCodeIdByName $$
CREATE FUNCTION dbname.getCodeIdByName(findCode VARCHAR(100) ) RETURNS
VARCHAR(20)
BEGIN
  DECLARE getName VARCHAR(20);
  SET getName = NULL;
  SELECT CODE_ID_DET INTO getName FROM COM_CODE_DET WHERE CODE_NM_DET=
findCode;
  RETURN getName;
END $$
delimiter ;
```

| | | | |
|------|---------|------------------|-------|
| SQL | DBeaver | CTRL+ENTER(sql) | ALT + |
| X() | | | |

MariaDB

```
[mysql@dev tmp]$ mysql_upgrade -u root -p
```

DATA

TIMESTAMPDIFF

- - `TIMESTAMPDIFF(, 1, 2);`
- - SECOND :
 - MINUTE :
 - HOUR :
 - DAY :
 - WEEK :
 - MONTH :
 - QUARTER :
 - YEAR :
- ()
 - : `SELECT TIMESTAMPDIFF(MINUTE, '2017-03-01', '2018-03-28');`
 - : 564480

CONCAT

```
SELECT  
  aei.ABILITYUNIT_EL_NM  
  , group_concat(arr.RES_ROLES separator '|') AS RES_ROLES_RES  
  , aei.AUE_CD  
FROM  
  ABILITYUNIT_INFO ai  
GROUP BY aei.ABILITYUNIT_EL_NM
```

| row | RES_ROLES | row | RES_ROLES_RES | select |
|-----|-----------|-----|---------------|--------|
|-----|-----------|-----|---------------|--------|

()

```
SELECT boardno, account, subject, content, createdate  
FROM board  
ORDER BY boardno DESC  
LIMIT 0, 10
```

```
SELECT boardno, account, subject, content, createdate  
FROM board  
ORDER BY boardno DESC
```

```
LIMIT 10 OFFSET 0
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} LIKE ${OLD_TABLE}
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} ( SELECT * FROM ${OLD_TABLE} )
```

```
INSERT INTO ${DEST_TABLE} ( SELECT * FROM ${SOURCE_TABLE} )
```

Encoding

- [latin1](#) [utf8mb4](#)

Logging

[log](#) [_](#)

Migration To Oracle

SQL Developer [autoincrement](#)

- [MySQL to Oracle Migration](#)

Trouble Shooting

- [TIMEZONE error](#)

Ref

- [MySQL](#) [\(Table Copy \)](#)
- [MariaDB](#) [\(CentOS 7\)](#)
- [CentOS7 MariaDB](#)
- [RHEL/CentOS, Ubuntu](#) [MySQL 5.6, 5.7](#)
- [- -](#) [\[PostIT\]](#)

- [MariaDB] root
 - MySQL root
 - SQL Developer MySQL
 - [MySQL] 가 (DATEDIFF, TIMESTAMPDIFF)
- , , , eleven, mariadb, mysql

From: <http://125.132.25.164/dokuwiki/> -

. - 2023.12

Permanent link: <http://125.132.25.164/dokuwiki/doku.php?id=wiki:database:mariadb&rev=1600072299>

Last update: **2022/03/10 19:52**

