

Mysql / MariaDB

- description : MariaDB, Mysql
- author :
- email : dhan@repia.com
- lastupdate : 2020-02-08

•

FAQ

/

CentOS7

```
//  
[mysql@dev tmp]$ systemctl status mariadb  
  
//  
[mysql@dev tmp]$ systemctl enable mariadb  
  
// MariaDB  
[mysql@dev tmp]$ systemctl restart mariadb
```

, Dump

MariaDB
mysqldump
mysqldump
[Project :: Server] MariaDB

Mysql DB

user table

가

```
INSERT INTO mysql.`user`  
(Host, `User`, Password, Select_priv, Insert_priv, Update_priv, Delete_priv,  
Create_priv, Drop_priv, Reload_priv, Shutdown_priv, Process_priv, File_priv,  
Grant_priv, References_priv, Index_priv, Alter_priv, Show_db_priv,  
Super_priv, Create_tmp_table_priv, Lock_tables_priv, Execute_priv,  
Repl_slave_priv, Repl_client_priv, Create_view_priv, Show_view_priv,  
Create_routine_priv, Alter_routine_priv, Create_user_priv, Event_priv,  
Trigger_priv, Create_tablespace_priv, ssl_type, ssl_cipher, x509_issuer,  
x509_subject, max_questions, max_updates, max_connections,  
max_user_connections, plugin, authentication_string, password_expired,  
is_role)  
VALUES('%', '__user__', password('__password__'), 'Y', 'Y', 'Y', 'Y', 'Y',  
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',  
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',  
'Y', 'N', 'N')  
;
```

db table 가

```
INSERT INTO mysql.db  
(Host, Db, `User`, Select_priv, Insert_priv, Update_priv, Delete_priv,  
Create_priv, Drop_priv, Grant_priv, References_priv, Index_priv, Alter_priv,  
Create_tmp_table_priv, Lock_tables_priv, Create_view_priv, Show_view_priv,  
Create_routine_priv, Alter_routine_priv, Execute_priv, Event_priv,  
Trigger_priv)  
VALUES('%', '__db__', '__user__', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',  
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y');
```

FLUSH privileges;

Maria DB

```
MariaDB [(none)]> create user '${User}'@'${Host}' identified by  
'${Password}';  
Query OK, 0 rows affected (0.00 sec)
```

EX : create user @'127.0.0.1' identified by '12';

Host : IP

Tip : IP 3가 .

- @'127.0.0.1'
- @'localhost'
- @' IP' | 가 IP

(\${DB})

```
MariaDB [(none)]> grant all privileges on ${DB}.* to '${User}'@'${Host}';
Query OK, 0 rows affected (0.00 sec)
```

EX : grant all privileges on repia.* to ' ' @'localhost';

Tip : grant all -

- all select, update, create

```
MariaDB [(none)]> flush privileges;
Query OK, 0 rows affected (0.00 sec)
```

Tip :

- :: MySQL 가
- MariaDB 10.4 user

LOCK, UNLOCK

```
ALTER USER '${User}'@'${Host}' ACCOUNT LOCK;
ALTER USER '${User}'@'${Host}' ACCOUNT UNLOCK;
```

MySQL, MariaDB DB, ,
 [mysql] mysql, mariaDB , 가
 Account Locking

Windows 가
 Table \${Table name} doesn't exist

Windows ,
 , Linux Linux

- mariadb /etc/my.cnf lower_case_table_names = 1 가

value	meaning		
0	CREATE TABLE	CREATE DATABASE	
	SELECT Insert 가	Windows/Mac OS X	OS
1	DB 가	DB	가
2	CREATE TABLE	CREATE DATABASE	가 OS(Mac OS X)

가
DATABASE
dump

(function)

```
[      ]
mysql> SHOW PROCEDURE STATUS

[      ]
mysql> SHOW CREATE PROCEDURE uso_Get_Mini_Evaluation

[      ]
mysql> SHOW CREATE VIEW v_core_ability_examination
```

MySQL

- ID,CD NAME
- delimiter() (X)

```
delimiter $$

DROP FUNCTION IF EXISTS dbname.getCodeIdByName $$

CREATE FUNCTION dbname.getCodeIdByName(findCode VARCHAR(100) ) RETURNS
VARCHAR(20)
BEGIN
    DECLARE getName VARCHAR(20);
    SET getName = NULL;
    SELECT CODE_ID_DET  INTO getName FROM COM_CODE_DET WHERE CODE_NM_DET=
findCode;
    RETURN getName;
END $$
```

delimiter ;

SQL	DBeaver	CTRL+ENTER(sql)	ALT +
X()		.

MariaDB

```
[mysql@dev tmp]$ mysql_upgrade -u root -p
```

DATA

TIMESTAMPDIFF

- - **TIMESTAMPDIFF**(, 1, 2);
- - SECOND :
 - MINUTE :
 - HOUR :
 - DAY :
 - WEEK :
 - MONTH :
 - QUARTER :
 - YEAR :
- ()
 - : SELECT TIMESTAMPDIFF(MINUTE, '2017-03-01', '2018-03-28');
 - : 564480

CONCAT

```
SELECT
  aei.ABILITYUNIT_EL_NM
, group_concat(arr.RES_ROLES separator '|') AS RES_ROLES_RES
, aei.AUE_CD
FROM
  ABILITYUNIT_INFO ai
GROUP BY aei.ABILITYUNIT_EL_NM
```

row	RES_ROLES	row	RES_ROLES_RES	select
------------	------------------	------------	----------------------	---------------

()

```
SELECT boardno, account, subject, content, createdate
FROM board
ORDER BY boardno DESC
LIMIT 0, 10
```

```
SELECT boardno, account, subject, content, createdate
FROM board
ORDER BY boardno DESC
LIMIT 10 OFFSET 0
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} LIKE ${OLD_TABLE}
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} ( SELECT * FROM ${OLD_TABLE} )
```

```
INSERT INTO ${DEST_TABLE} ( SELECT * FROM ${SOURCE_TABLE} )
```

Encoding

- latin1 utf8mb4

Logging

log _

Migration To Oracle

SQL Developer autoincrement

- MySQL to Oracle Migration

Trouble Shooting

- TIMEZONE error
- IP MySQL(MariaDB)

- |MYSQL(MariaDB)
'192.168.X.X'(10061) .(Feat. Can't Connect To MySQL Server On

Ref

- MySQL (Table Copy)
 - MariaDB (CentOS 7)
 - CentOS7 MariaDB
 - RHEL/CentOS, Ubuntu MySQL 5.6, 5.7
 - - - - [PostIT]
 - [MariaDB] root
 - MySQL root
 - SQL Developer MySQL
 - [MySQL] 가 (DATEDIFF, TIMESTAMPDIFF)
 - MySQL (MariaDB)
- , , eleven, mariadb, mysql

From:

<http://125.132.25.164/dokuwiki/> -

. - 2023.12



Permanent link:

<http://125.132.25.164/dokuwiki/doku.php?id=wiki:database:mariadb&rev=1649047618>

Last update: **2022/04/04 13:46**