

Mysql / MariaDB

- description : MariaDB, Mysql
- author :
- email : dhan@repia.com
- lastupdate : 2020-02-08

•

FAQ

/

CentOS7

```
//
[mysql@dev tmp]$ systemctl status mariadb

//
[mysql@dev tmp]$ systemctl enable mariadb

// MariaDB
[mysql@dev tmp]$ systemctl restart mariadb
```

, Dump

[MariaDB](#)
[mysqldump](#)
[mysqldump](#)
[\[Project :: Server\] MariaDB](#)

(, , ,)

- @'127.0.0.1'
- @'localhost'
- @' IP' | 가 IP

(\${DB })

```
MariaDB [(none)]> grant all privileges on ${DB }.* to '${User }'@'${Host }';
Query OK, 0 rows affected (0.00 sec)
```

EX : grant all privileges on repia.* to ' '@'localhost';
 Tip : grant all -

- all select, update, create .

```
MariaDB [(none)]> flush privileges;
Query OK, 0 rows affected (0.00 sec)
```

Tip :

- :: MySQL 가
- MariaDB 10.4 user

LOCK, UNLOCK

```
ALTER USER '${User }'@'${Host }' ACCOUNT LOCK;
ALTER USER '${User }'@'${Host }' ACCOUNT UNLOCK;
```

MySQL, MariaDB DB, , 가
 [mysql] mysql, mariaDB , 가
 Account Locking

Windows 가 가 .
 Table \${Table name} doesn't exist

Windows , Linux .
 , Linux .

• mariadb /etc/my.cnf lower_case_table_names = 1 가

value	meaing
0	CREATE TABLE CREATE DATABASE SELECT Insert OS 가 Windows/Mac OS X
1	가 DB DB 가
2	CREATE TABLE CREATE DATABASE 가 OS(Mac OS X)

가
DATABASE
dump
(, ,)

```
// (SHOW INDEX FROM )
$> SHOW INDEX FROM HEQMS.TB_HFDMS2_STD_CMPTN_SD;
// (ALTER TABLE DROP INDEX )
$> ALTER TABLE HEQMS.TB_HFDMS2_STD_CMPTN_SD DROP INDEX
IX_TB_HEQMS2_STD_JOB_CMPTN_SD_01;
// (CREATE INDEX ON ( ))
$> CREATE INDEX IX_TB_HFDMS2_STD_CMPTN_SD_01 USING BTREE ON
TB_HFDMS2_STD_CMPTN_SD (STD_NO);
$> CREATE INDEX IX_TB_HFDMS2_STD_CMPTN_SD_02 USING BTREE ON
TB_HFDMS2_STD_CMPTN_SD (STD_NO, DGNSS_ROUND);
```

(function)

```
[ ]
mysql> SHOW PROCEDURE STATUS

[ ]
mysql> SHOW CREATE PROCEDURE uso_Get_Mini_Evaluation

[ ]
mysql> SHOW CREATE VIEW v_core_ability_examination
```

MySQL

- ID,CD NAME
- delimiter() (X)

```
delimiter $$
DROP FUNCTION IF EXISTS dbname.getCodeIdByName $$
CREATE FUNCTION dbname.getCodeIdByName(findCode VARCHAR(100) ) RETURNS
VARCHAR(20)
BEGIN
  DECLARE getName VARCHAR(20);
  SET getName = NULL;
  SELECT CODE_ID_DET INTO getName FROM COM_CODE_DET WHERE CODE_NM_DET=
findCode;
  RETURN getName;
END $$
delimiter ;
```

SQL DBeaver CTRL+ENTER(sql) ALT +
X() .

MariaDB

```
[mysql@dev tmp]$ mysql_upgrade -u root -p
```

DATA

TIMESTAMPDIFF

- - TIMESTAMPDIFF(, 1, 2);
- - SECOND :
 - MINUTE :
 - HOUR :
 - DAY :
 - WEEK :
 - MONTH :
 - QUARTER :
 - YEAR :
- ()
 - : SELECT TIMESTAMPDIFF(MINUTE, '2017-03-01', '2018-03-28');
 - : 564480

CONCAT



```
SELECT
  aei.ABILITYUNIT_EL_NM
  , group_concat(arr.RES_ROLES separator '|') AS RES_ROLES_RES
  , aei.AUE_CD
FROM
  ABILITYUNIT_INFO ai
GROUP BY aei.ABILITYUNIT_EL_NM
```

row RES_ROLES row RES_ROLES_RES select

()

```
SELECT boardno, account, subject, content, createdate
FROM board
ORDER BY boardno DESC
LIMIT 0, 10
```

```
SELECT boardno, account, subject, content, createdate
FROM board
ORDER BY boardno DESC
LIMIT 10 OFFSET 0
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} LIKE ${OLD_TABLE}
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} ( SELECT * FROM ${OLD_TABLE} )
```

```
INSERT INTO ${DEST_TABLE} ( SELECT * FROM ${SOURCE_TABLE} )
```

Encoding

- latin1 utf8mb4

Logging

log _

Migration To Oracle

SQL Developer autoincrement

- [MySQL to Oracle Migration](#)

Trouble Shooting

- [TIMEZONE error](#)
- [IP MySQL\(MariaDB\)](#)
- [MYSQL\(MariaDB\) '192.168.X.X'\(10061\) \(Feat. Can't Connect To MySQL Server On](#)

Ref

- [MySQL \(Table Copy \)](#)
- [MariaDB \(CentOS 7\)](#)
- [CentOS7 MariaDB](#)
- [RHEL/CentOS, Ubuntu MySQL 5.6, 5.7](#)
- [\[PostIT\]](#)
- [\[MariaDB\] root](#)
- [MySQL root](#)
- [SQL Developer MySQL](#)
- [\[MySQL\] 가 \(DATEDIFF, TIMESTAMPDIFF \)](#)
- [MySQL \(MariaDB \)](#)

, , , eleven, mariadb, mysql

From: <http://125.132.25.164/dokuwiki/> -

. - 2023.12

Permanent link: <http://125.132.25.164/dokuwiki/doku.php?id=wiki:database:mariadb&rev=1651655683>

Last update: **2022/05/04 18:14**

