

Mysql / MariaDB

- description : MariaDB, Mysql
- author :
- email : dhan@repia.com
- lastupdate : 2020-02-08

•

FAQ

/

CentOS7

```
//
[mysql@dev tmp]$ systemctl status mariadb

//
[mysql@dev tmp]$ systemctl enable mariadb

// MariaDB
[mysql@dev tmp]$ systemctl restart mariadb
```

, Dump

[MariaDB](#)
[mysqldump](#)
[mysqldump](#)
[\[Project :: Server\] MariaDB](#)

(, , ,)

Mysql DB

user table 가

```
INSERT INTO mysql.`user`
(Host, `User`, Password, Select_priv, Insert_priv, Update_priv, Delete_priv,
Create_priv, Drop_priv, Reload_priv, Shutdown_priv, Process_priv, File_priv,
Grant_priv, References_priv, Index_priv, Alter_priv, Show_db_priv,
Super_priv, Create_tmp_table_priv, Lock_tables_priv, Execute_priv,
Repl_slave_priv, Repl_client_priv, Create_view_priv, Show_view_priv,
Create_routine_priv, Alter_routine_priv, Create_user_priv, Event_priv,
Trigger_priv, Create_tablespace_priv, ssl_type, ssl_cipher, x509_issuer,
x509_subject, max_questions, max_updates, max_connections,
max_user_connections, plugin, authentication_string, password_expired,
is_role)
VALUES('%', '__user__', password('__password__'), 'Y', 'Y', 'Y', 'Y', 'Y',
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y',
'', '', '', '', '0', '0', '0', '0', '',
'', 'N', 'N')
;
```

db table 가

```
INSERT INTO mysql.db
(Host, Db, `User`, Select_priv, Insert_priv, Update_priv, Delete_priv,
Create_priv, Drop_priv, Grant_priv, References_priv, Index_priv, Alter_priv,
Create_tmp_table_priv, Lock_tables_priv, Create_view_priv, Show_view_priv,
Create_routine_priv, Alter_routine_priv, Execute_priv, Event_priv,
Trigger_priv)
VALUES('%', '__db__', '__user__', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'N', 'Y',
'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y', 'Y');
```

```
FLUSH privileges;
```

Maria DB

```
MariaDB [(none)]> create user '${User }'@'${Host }' identified by
'${Password }';
Query OK, 0 rows affected (0.00 sec)
```

EX : create user @'127.0.0.1' identified by ' 12';
Host : IP
Tip : IP 3가 .

- @'127.0.0.1'
- @'localhost'
- @' IP' | 가 IP

(\${DB })

```
MariaDB [(none)]> grant all privileges on ${DB }.* to '${User }'@'${Host }';
Query OK, 0 rows affected (0.00 sec)
```

EX : grant all privileges on repia.* to ' '@'localhost';
 Tip : grant all -

- all select, update, create .

```
MariaDB [(none)]> flush privileges;
Query OK, 0 rows affected (0.00 sec)
```

Tip :

- :: MySQL 가
- MariaDB 10.4 user

LOCK, UNLOCK

```
ALTER USER '${User }'@'${Host }' ACCOUNT LOCK;
ALTER USER '${User }'@'${Host }' ACCOUNT UNLOCK;
```

MySQL, MariaDB DB, , 가
 [mysql] mysql, mariaDB , 가
 Account Locking

Windows 가 가 .
 Table \${Table name} doesn't exist

Windows , Linux .
 , Linux .

• mariadb /etc/my.cnf lower_case_table_names = 1 가

value	meaing
0	CREATE TABLE CREATE DATABASE SELECT Insert OS 가 Windows/Mac OS X
1	가 DB DB 가
2	CREATE TABLE CREATE DATABASE 가 OS(Mac OS X)

가
DATABASE
dump
(, ,)

```
// (SHOW INDEX FROM )
$> SHOW INDEX FROM HEQMS.TB_HFDMS2_STD_CMPTN_SD;
// (ALTER TABLE DROP INDEX )
$> ALTER TABLE HEQMS.TB_HFDMS2_STD_CMPTN_SD DROP INDEX
IX_TB_HEQMS2_STD_JOB_CMPTN_SD_01;
// (CREATE INDEX ON ( ))
$> CREATE INDEX IX_TB_HFDMS2_STD_CMPTN_SD_01 USING BTREE ON
TB_HFDMS2_STD_CMPTN_SD (STD_NO);
$> CREATE INDEX IX_TB_HFDMS2_STD_CMPTN_SD_02 USING BTREE ON
TB_HFDMS2_STD_CMPTN_SD (STD_NO, DGNSS_ROUND);
// & 가
$> ALTER TABLE RSA.SIMS_MONITORING DROP INDEX IX_SIMS_MONITORING_01;
$> CREATE UNIQUE INDEX IX_SIMS_MONITORING_01 USING BTREE ON
RSA.SIMS_MONITORING (MONIT_ID);
//
$> ALTER TABLE RSA.SIMS_MONITORING DROP INDEX `PRIMARY`;
```

(function)

```
[ ]
mysql> SHOW PROCEDURE STATUS
[ ]
```

```
mysql> SHOW CREATE PROCEDURE uso_Get_Mini_Evaluation
[
]
mysql> SHOW CREATE VIEW v_core_ability_examination
```

MySQL

- ID,CD NAME (X)
- delimiter()

```
delimiter $$
DROP FUNCTION IF EXISTS dbname.getCodeIdByName $$
CREATE FUNCTION dbname.getCodeIdByName(findCode VARCHAR(100) ) RETURNS
VARCHAR(20)
BEGIN
  DECLARE getName VARCHAR(20);
  SET getName = NULL;
  SELECT CODE_ID_DET INTO getName FROM COM_CODE_DET WHERE CODE_NM_DET=
findCode;
  RETURN getName;
END $$
delimiter ;
```

SQL DBever CTRL+ENTER(sql) ALT +
X() .

MariaDB

```
[mysql@dev tmp]$ mysql_upgrade -u root -p
```

DATA

TIMESTAMPDIFF

- - TIMESTAMPDIFF(, 1, 2);
- - SECOND :
 - MINUTE :
 - HOUR :
 - DAY :
 - WEEK :
 - MONTH :
 - QUARTER :
 - YEAR :
- ()

- : SELECT TIMESTAMPDIFF(MINUTE, '2017-03-01', '2018-03-28');
- : 564480

CONCAT

```
SELECT
  aei.ABILITYUNIT_EL_NM
  , group_concat(arr.RES_ROLES separator '|') AS RES_ROLES_RES
  , aei.AUE_CD
FROM
  ABILITYUNIT_INFO ai
GROUP BY aei.ABILITYUNIT_EL_NM
```

row	RES_ROLES	row	RES_ROLES_RES	select
-----	-----------	-----	---------------	--------

()

```
SELECT boardno, account, subject, content, createdate
FROM board
ORDER BY boardno DESC
LIMIT 0, 10
```

```
SELECT boardno, account, subject, content, createdate
FROM board
ORDER BY boardno DESC
LIMIT 10 OFFSET 0
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} LIKE ${OLD_TABLE}
```

(SCHEMA)

```
CREATE TABLE ${NEW_TABLE} ( SELECT * FROM ${OLD_TABLE} )
```

```
INSERT INTO ${DEST_TABLE} ( SELECT * FROM ${SOURCE_TABLE} )
```

Function & Procedures

-

Encoding

- latin1 utf8mb4

Logging

log _

Migration To Oracle

SQL Developer autoincrement

- [MySQL to Oracle Migration](#)

Trouble Shooting

- TIMEZONE error
- IP MySQL(MariaDB)
- |MYSQL(MariaDB) (Feat. Can't Connect To MySQL Server On '192.168.X.X'(10061)

Ref

- MySQL (Table Copy)
- MariaDB (CentOS 7)
- CentOS7 MariaDB
- RHEL/CentOS, Ubuntu MySQL 5.6, 5.7
- - - [PostIT]
- [MariaDB] root
- MySQL root
- SQL Developer MySQL
- [MySQL] 가 (DATEDIFF, TIMESTAMPDIFF)
- MySQL (MariaDB)

MySQL Note

- [MySQL note](#)

, , , [eleven](#), [mariadb](#), [mysql](#)

From:
<http://125.132.25.164/dokuwiki/> -

. - 2023.12

Permanent link:
<http://125.132.25.164/dokuwiki/doku.php?id=wiki:database:mariadb&rev=1673603050>

Last update: **2023/01/13 18:44**

