SQL

- description : SQL 관련 자료 등록
- author : 주레피
- email : dhan@repia.com
- lastupdate : 2020-03-18

CASE...WHEN...THEN

[DBMS_Oracle] CASE..WHEN...THEN
[MySQL] CASE 기본 사용법

Date

Oracle : sysdate

```
    SELECT sysdate FROM dual;
```

MariaDB, Mysql : now()

```
    SELECT now() FROM dual;
```

Distinct

[Oracle SQL] DISTINCT 키워드

Where

IN 조건

```
SELECT user_num  ,  user_id , user_mobile , user_gender , user_amount  ,
user_addr
    FROM  User_Table
    WHERE user_id  IN ('user1','user3')
    ORDER BY user_num DESC;
```

위와 같이 하나의 Column에서 다수의 데이터를 Select 해야 할 시에 WHERE IN 조건을 사용한다.

Ref

오라클의 sysdate와 같은 mysql혹은 mariadb의 함수?

Tip

- [MySQL/Oracle] max, min 값을 가진 row select 하기
- [SQL] 서브 쿼리의 개념과 별칭(ALIAS) 사용하기

Troubleshooting

- U115: Subquery in FROM must have an alias

주레피, sql, 천호동밤안개

From:
http://125.132.25.164/dokuwiki/ - **문제를 잘 정의하는 것은 문제를 절반 해결한 것이다. - 2023.12**

Permanent link:
http://125.132.25.164/dokuwiki/doku.php?id=wiki:database:sql&rev=1585801159

Last update: **2022/03/10 19:52**