Resin

- description : Resin과 관련된 내용 기술
- author : 주레피
- email : dhan@repia.com
- lastupdate : 2020-06-04

Jndi 설정법

jndi(Java Naming and Directory interface) 설정 *Was Server 마다 넣는 위치와 포맷이 다름* <code xml> <database> <jndi-name>jdbc/mysql</jndi-name> <driver type="com.mysql.jdbc.Driver"> <url>jdbc:mysql:localhost:3306/database</url>

```
  <user>user</user>
  <password>password</password>
</driver>
<prepared-statement-cache-size>64</prepared-statement-cache-size>
<max-connections>20</max-connections>
<max-idle-time>30s</max-idle-time>
```

</database>

<database>

```
<jndi-name>jdbc/oracle</jndi-name>
<driver type="oracle.jdbc.pool.OracleConnectionPoolDataSource">
  <url>jdbc:oracle:thin:@127.0.0.1:1521:xe</url>
  <user>user</user>
  <password>password</password>
  <connectionProperties>
    <SetBigStringTryClob>true</SetBigStringTryClob>
  </connectionProperties>
</driver>
```

```
<prepared-statement-cache-size>64</prepared-statement-cache-size>
<max-connections>20</max-connections>
<max-idle-time>30s</max-idle-time>
```

</database>

<database>

```
<jndi-name>jdbc/mssql</jndi-name>
<driver type="com.microsoft.sqlserver.jdbc.SQLServerDriver">
  <url>jdbc:sqlserver:// 127.0.0.1:1433;DatabaseName=database</url>
```

```
  <user>user</user>
  <password>password</password>
</driver>
<prepared-statement-cache-size>64</prepared-statement-cache-size>
<max-connections>20</max-connections>
<max-idle-time>30s</max-idle-time>
```

</database>

<database>

```
<jndi-name>jdbc/db2</jndi-name>
<driver type="com.ibm.db2.jcc.DB2Driver">
  <url>jdbc:db2://127.0.0.1:50000/database</url>
  <user>user</user>
  <password>password</password>
</driver>
<prepared-statement-cache-size>64</prepared-statement-cache-size>
<max-connections>20</max-connections>
<max-idle-time>30s</max-idle-time>
```

</database> </code>
사용 예시

```
<%@ page contentType="text/html; charset=utf-8" %>
<%@ page import="javax.naming.*, java.sql.*, javax.sql.*" %>
<%
String jndi = "java:comp/env/jdbc/mysql";
InitialContext ctx = new InitialContext();     // 현재 실행중인 등록된 컨텍스트를 가져옴
DataSource ds = (DataSource)ctx.lookup(jndi); // 데이터소스 획득

Connection conn = null;
Statement stmt = null;
ResultSet rs = null;

try
{
   conn = ds.getConnection();
   stmt = conn.createStatement();
   rs = stmt.executeQuery("SELECT name, email, age FROM tb_user");
   while(rs.next())
   {
      out.println(rs.getString("name") + "<br>");
   }

}
catch(Exception e)
{
   out.print(e);
}
```

```
finally // 리소스 반환
{
   if(rs != null) rs.close(); rs = null;
   if(stmt != null) stmt.close(); stmt = null;
   if(conn != null) conn.close(); conn = null;
}
%>
```

Tip

Troubleshooting

Ref

레진(Resin)에서 데이터베이스 연동하기

주레피

From:
http://125.132.25.164/dokuwiki/ - **문제를 잘 정의하는 것은 문제를 절반 해결한 것이다. - 2023.12**

Permanent link:
http://125.132.25.164/dokuwiki/doku.php?id=wiki:eclipse:resin&rev=1591232720

Last update: **2022/03/10 19:52**