

data-* attributes

- description : data-* attributes
- author :
- email : shlim@repia.com
- lastupdate : 2022-06-22 Wed

data-* attributes

:WHATWG (Web Hypertext Application Technology Working Group)

HTML ()

3.2.6.6 Embedding custom non-visible data with the data-* attributes

A custom data attribute is an attribute in no namespace whose name starts with the string "data-", has at least one character after the hyphen, is XML-compatible, and contains no ASCII upper alphas.

Note:

All attribute names on HTML elements in HTML documents get ASCII-lowercased automatically, so the restriction on ASCII uppercase letters doesn't affect such documents.

Custom data attributes are intended to store custom data, state, annotations, and similar, private to the page or application, for which there are no more appropriate attributes or elements.

These attributes are not intended for use by software that is not known to the administrators of the site that uses the attributes. For generic extensions that are to be used by multiple independent tools, either this specification should be extended to provide the feature explicitly, or a technology like microdata should be used (with a standardized vocabulary).

3.2.6.6 data-*

, 가 XML "data-" ASCII upper alphas .

Note: [HTML documents](#) [HTML elements](#) ASCII 가 , ASCII .

, ' 가 '

(') .

An [ASCII upper alpha](#) is a code point in the range U+0041 (A) to U+005A (Z), inclusive.

A [code point](#) is a Unicode code point and is represented as “U+” followed by four-to-six ASCII upper hex digits, in the range U+0000 to U+10FFFF, inclusive. A code point’s value is its underlying number.

Ref Link

[Embedding custom non-visible data with the data-* attributes](#)

., data-*

From: <http://125.132.25.164/dokuwiki/> -

. - 2023.12

Permanent link: http://125.132.25.164/dokuwiki/doku.php?id=wiki:html:html_note:data-_attributes&rev=1655897314

Last update: **2022/06/22 20:28**

