

JavaScript String Methods

- description : JavaScript String Methods
- author :
- email : shlim@repia.com
- lastupdate : 2021-04-23

The source of this article

[JavaScript String Methods](#)

String Methods and Properties

"John Doe" (Primitive values) 가 (가).

JavaScript ,
JavaScript ,

String Length

length .

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Properties</h2>
  <p>The length property returns the length of a string</p>
  <p id="demo"></p>
  <script>
    let txt = "ABCDEFGHIJKLMNOPQRSTUVWXYZ";
    let sln = txt.length;
    document.getElementById("demo").innerHTML = sln;
  </script>
</body>
</html>
```

Finding a String in a String

`indexOf()` _____(occurrence) ()

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>The indexOf() method returns the position of the first occurrence of a
specified text:</p>
  <p id="demo"></p>
  <script>
    let str = "Please locate where 'locate' occurs!";
    let pos = str.indexOf("locate");
    document.getElementById("demo").innerHTML = pos; // 7
  </script>
</body>
</html>
```

```
%%JavaScript%% 0
0 , 1 , 2 ...
```

`lastIndexOf()` 가 ()

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>The lastIndexOf() method returns the positon of the last occurrence of
a specified text:</p>
  <p id="demo"></p>
  <script>
    let str = "Please locate where 'locate' occurs!";
    let pos = str.lastIndexOf('locate');
    document.getElementById("demo").innerHTML = pos; // 21
  </script>
</body>
</html>
```

가 , `indexOf()` `lastIndexOf()` -1 .

```
<!DOCTYPE html>
```

```

<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>Both indexOf() and lastIndexOf() returns -1 if the text is not
found:</p>
  <p id="demo"></p>
  <script>
    let str = "Please locate where 'locate' occurs!";
    let pos = str.indexOf("John");
    document.getElementById("demo").innerHTML = pos; // -1
  </script>
</body>
</html>

```

```

<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>The indexOf() method accepts a second parameter as the starting
position for the search:</p>
  <p id="demo"></p>
  <script>
    let str = "Please locate where 'locate' occurs!";
    let pos = str.indexOf("locate", 15); //index[15]
    document.getElementById("demo").innerHTML = pos; // 21
  </script>
</body>
</html>

```

lastIndexOf() () .
 , 가 15 , 15 , .

```

<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>The lastIndexOf() method accepts a second parameter as the starting
position for the search.</p>
  <p>Remember that the lastIndexOf() method searches backwards, so position
15 means start the search at position 15, and search to the beginning.</p>
  <p>Position 15 is position 15 from the beginning</p>
  <p id="demo"></p>
  <script>
    let str = "Please locate where 'locate' occurs!";
    let pos = str.lastIndexOf("locate", 15);
    document.getElementById("demo").innerHTML = pos; // 7
    console.log(str.length); // 36
  </script>
</body>
</html>

```

```

        console.log(str[15]);          // h
    </script>
</body>
</html>

```

var = str	P	l	e	a	s	e		l	o	c	a	t	e		w	h	e	r	e		'	l	o	c	a	t	e		'		o	c	c	u	r	s	!
Index no	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	
Index no : 0 ~ 35 / length : 36																																					

Tip: `indexOf()` (index[0])

`searchValue`

Searching for a String in a String

```
search( )
```

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>The search() method returns the position of the first occurrence of a
specified text in a string.</p>
  <p id="demo"></p>
  <script>
    let str = "Please locate where 'locate' occurs!";
    let pos = str.search("locate");
    document.getElementById("demo").innerHTML = pos; // 7
  </script>
</body>
</html>
```

Did You Notice?

indexOf()	search()	?
()		?

가

- `search()`
- `indexOf()` ()

Extracting String Parts

3가

- slice(start, end)
- substring(start, end)
- substr(start, length)

The slice() Method

slice()

(,) 가

7 12 (13-1)

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>The slice() method extract a part of a string and returns the extracted
parts in a new string:</p>
  <p id="demo"></p>
  <script>
    let str = "Apple, Banana, Kiwi";
    let res = str.slice(7, 13); // 7- , 13- , X
    document.getElementById("demo").innerHTML = res; // Banana
  </script>
</body>
</html>
```

: 0 . 0 .

가 ,

-12 -6 .

```
<script>
  let str = "Apple, Banana, Kiwi";
  let res = str.slice(-12, -6);
  document.getElementById("demo").innerHTML = res;
  console.log(str.length);
</script>
```

가 from MDN:

```
str.slice(beginIndex[, endIndex])
```

```
beginIndex:
-
-           , beginIndex = str.length(           ) + beginIndex
- ) beginIndex = -3           ,           strLength + (-3)
endIndex:
- 0
- endIndex
```

(- > 가 가 , .

```
<script>
let str = "Apple, Banana, Kiwi";
let res = str.slice(7);
document.getElementById("demo").innerHTML = res; // Banana, Kiwi
</script>
```

가 , 가 .

```
<script>
let str = "Apple, Banana, Kiwi";
let res = str.slice(-12);
document.getElementById("demo").innerHTML = res; // Banana, Kiwi
</script>
```

Internet Explorer 8 가 .

The substring() Method

substring() slice() .

substring() .

```
<script>
let str = "Apple, Banana, Kiwi";
let res = str.substring(7, 13); // index7 12
document.getElementById("demo").innerHTML = res; // Banana
</script>
```

substring()

The substr() Method

substr() slice()

가

```
<script>
  let str = "Apple, Banana, Kiwi";
  let res = str.substr(7, 10);    // index7    10
  document.getElementById("demo").innerHTML = res;  // Banana, Ki
</script>
```

, substr()

```
<script>
  let str = "Apple, Banana, Kiwi";
  let res = str.substr(8);        // index7
  document.getElementById("demo").innerHTML = res;  // anana, Kiwi
</script>
```

가

```
<script>
  let str = "Apple, Banana, Kiwi";
  let res = str.substr(-8);        // index-8
  document.getElementById("demo").innerHTML = res;  // na, Kiwi
</script>
```

Replacing String Content

replace()

()

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>Replace "Microsoft" with "W3Schools" in the paragraph below:</p>
  <button onclick="myFunction()">Try it</button>
  <p id="demo">Please visit Microsoft!</p>
  <script>
    function myFunction() {
      let str = document.getElementById("demo").innerHTML;
      let txt = str.replace("Microsoft", "W3Schools");
```

```
document.getElementById("demo").innerHTML = txt;
}
</script>
</body>
</html>
```

`'replace()'`

`, replace()`

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>Replace "Microsoft" with "W3Schools" in the paragraph below:</p>
  <button onclick="myFunction()">Try it</button>
  <p id="demo">Please visit Microsoft and Microsoft!</p>
  <script>
    function myFunction() {
      let str = document.getElementById("demo").innerHTML;
      let txt = str.replace("Microsoft", "W3Schools");
      document.getElementById("demo").innerHTML = txt;
    }
  </script>
</body>
</html>
```

`replace()`

`MICROSOFT`

```
<!DOCTYPE html>
<html>
<body>
  <h2>JavaScript String Methods</h2>
  <p>Try to replace "Microsoft" with "W3Schools" in the paragraph below:</p>
  <button onclick="myFunction()">Try it</button>
  <p id="demo">Please visit Microsoft!</p>
  <script>
    function myFunction() {
      let str = document.getElementById("demo").innerHTML;
      let txt = str.replace("MICROSOFT", "W3Schools");
      document.getElementById("demo").innerHTML = txt;
    }
  </script>
```

```
<P><strong>Note:</strong> Nothing will happen. By default, the replace()
method is case sensitive. Writing MICROSOFT (with upper-case) will not
work.</P>
</body>
</html>
```

```
, /i ( ) .
```

```
<script>
function myFunction() {
  let str = document.getElementById("demo").innerHTML;
  let txt = str.replace(/MICROSOFT/i, "W3Schools");
  document.getElementById("demo").innerHTML = txt;
}
</script>
```

```
, /g ( ) .
```

```
<script>
function myFunction() {
  let str = document.getElementById("demo").innerHTML;
  let txt = str.replace(/Microsoft/g, "W3Schools");
  document.getElementById("demo").innerHTML = txt;
}
</script>
```

global match & case-insensitive

```
<script>
function myFunction() {
  let str = document.getElementById("demo").innerHTML;
  let txt = str.replace(/MiCROSOFT/gi, "W3Schools");
  document.getElementById("demo").innerHTML = txt;
}
</script>
```

Converting to Upper and Lower Case

```
toUpperCase() .
```

```
<!DOCTYPE html>
```

```
<html>
<body>
  <p>Convert string to upper case:</p>
  <button onclick="myFunction()">Try it</button>
  <p id="demo">Bonjour le Monde</p>
  <script>
    function myFunction() {
      let text = document.getElementById("demo").innerHTML;
      document.getElementById("demo").innerHTML = text.toUpperCase();
    }
  </script>
</body>
</html>
```

toLowerCase()

```
<script>
  function myFunction() {
    let text = document.getElementById("demo").innerHTML;
    document.getElementById("demo").innerHTML = text.toLowerCase();
  }
</script>
```

The concat() Method

concat()

```
<script>
  let text1 = "Impossible is";
  let text2 = "Nothing";
  let text3 = text1.concat(" ", text2); // // text1+ +text2
  document.getElementById("demo").innerHTML = text3; // Impossible is
  Nothing
</script>
```

concat()

```
var text = "Hello" + " " + "World!";
var text = "Hello".concat(" ", "World!");
```

: (immutable) : , 가 .

String.trim()

trim()

```
<script>
  function myFunction() {
    let str = "   Hello World!   ";
    alert(str.trim());
  }
</script>
```

Internet Explorer 8 trim () 가 .

IE 8 , replace() .

replace JavaScript String.prototype 가

JavaScript String Padding

ECMAScript 2017 가 String padStart padEnd 가

Internet Explorer .

Firefox Safari JavaScript .

Extracting String Characters

가 가 .

- charAt(position)

- `charCodeAt(position)`
- `[]`

The `charAt()` Method

`charAt()` () .

The `charCodeAt()` Method

`charCodeAt()` .

UTF-16 (0 65535) .

Property Access

ECMAScript 5 (2009) [] .

```
* Internet Explorer 7 가 .
*
* ( ).
* 가 , %%[]%% %%undefined%% , %%charAt()%%
*
* . %%str[0] = "A"%% !
```

Converting a String to an Array

`split()`

(separator)

가 ""

,

[0]

.

.\



Complete String Reference

, [Complete JavaScript String Reference](#)

가

, [Javascript, String, Methods](#)

From:
<http://125.132.25.164/dokuwiki/> -

. - 2023.12

Permanent link:
http://125.132.25.164/dokuwiki/doku.php?id=wiki:javascript:javascript_note:js_string_methods&rev=1619165432

Last update: **2022/03/10 19:52**

