jQuery Tutorial

- jQuery Intro
- jQuery Get Started
- jQuery Syntax
- jQuery Selectors
- even Selector
- jQuery Events

jQuery Effects

- jQuery Hide/Show
- jQuery Fade
- jQuery Slide
- jQuery Animate
- jQuery stop()
- jQuery Callback
- jQuery Chaining

jQuery HTML

- jQuery Get
- jQuery Set
- jQuery Add
- jQuery Remove
- jQuery CSS Classes
- jQuery css()
- jQuery Dimensions

jQuery Traversing

- jQuery Traversing
- jQuery Ancestors
- jQuery Descendants
- jQuery Siblings
- jQuery Filtering

jQuery AJAX

- jQuery AJAX Intro

- jQuery Load
- jQuery Get/Post

jQuery Misc

- jQuery noConflict()
- jQuery Filters

jQuery References

- jQuery References Selectors
  - jQuery * Selector
  - id Selector
  - jQuery .class Selector
  - jQuery multiple classes Selector
  - jQuery element Selector
  - jQuery multiple elements Selector
  - first Selector
  - last Selector
  - even Selector
  - odd Selector
  - first-child Selector
  - first-of-type Selector
  - last-child Selector
  - last-of-type Selector
  - nth-child() Selector
  - nth-last-child() Selector
  - nth-of-type() Selector
  - nth-last-of-type() Selector
  - only-child Selector
  - only-of-type Selector
- jQuery References Events
- jQuery References Effects
- jQuery References HTML/CSS
- jQuery References Traversing
- jQuery References AJAX
- jQuery References Misc
- jQuery References Properties

jQuery UI

- jQuery UI Sortable Widget

before, after, prepend, append

after()

The after() method inserts specified content after the selected elements.

after() 메소드는 선택된 요소의 뒤에 특정 내용을 삽입한다.

```
<div class="container">
  <h2>Greetings</h2>
  <div class="inner">Hello</div>
  <div class="inner">Goodbye</div>
</div>
```

```
$( ".inner" ).after( "<p>Test</p>" );
```

결과

```
<div class="container">
  <h2>Greetings</h2>
  <div class="inner">Hello</div>
  <p>Test</p>
  <div class="inner">Goodbye</div>
  <p>Test</p>
</div>
```

before()

The before() method inserts specified content in front of (before) the selected elements.

before() 메소드는 선택된 요소의 앞에 특정 내용을 삽입한다.

```
<div class="container">
  <h2>Greetings</h2>
  <div class="inner">Hello</div>
  <div class="inner">Goodbye</div>
</div>
```

```
$( ".inner" ).before( "<p>Je t'aime</p>" );
```

결과

```
<div class="container">
  <h2>Greetings</h2>
  <p>Je t'aime</p>
  <div class="inner">Hello</div>
  <p>Je t'aime</p>
  <div class="inner">Goodbye</div>
</div>
```

append()

The append() method inserts specified content at the end of the selected elements

append() 메소드는 선택된 요소의 끝(자식 요소)에 특정 내용을 삽입한다.

```
<h2>Greetings>/h2>
<div class="container">
    <div class="inner">Hello</div>
    <div class="inner">Goodbye</div>
</div>
```

```
$('.inner').append('<p>Test</p>');
```

결과

```
<h2>Greetings>/h2>
<div class="container">
    <div class="inner">
        Hello
        <p>Test</p>
    </div>
    <div class="inner">
        Goodbye
        <p>Test</p>
    </div>
</div>
```

prepend()

The prepend() method inserts specified content at the beginning of the selected elements.

prepend() 메소드는 선택된 요소의 시작(자식 요소)에 특정 내용을 삽입한다.

```
<h2>Greetings</h2>
<div class="container">
  <div class="inner">Hello</div>
  <div class="inner">Goodbye</div>
</div>
```

```
$( ".inner" ).prepend( "<p>Tiger</p>" );
```

결과

```
<h2>Greetings</h2>
<div class="container">
  <div class="inner">
    <p>Tiger</p>
    Hello
  </div>
  <div class="inner">
    <p>Tiger</p>
    Goodbye
  </div>
</div>
```

.attr(), .data() 관련 Link

- jQuery_.data()
- 확인, 정리 후 불필요한 링크 삭제
- jQuery data 값 변경
- jQuery 속성 관리 data()와 attr() 사용법 및 차이
- [JQUERY] DATA-XX 속성을 추가해주는 DATA() 함수에 대해
- jQuery.attr()
- jQuery.data()

From:
http://125.132.25.164/dokuwiki/ - **문제를 잘 정의하는 것은 문제를 절반 해결한 것이다. - 2023.12**

Permanent link:
http://125.132.25.164/dokuwiki/doku.php?id=wiki:javascript:jquery:jquery_note&rev=1666584845

Last update: **2022/10/24 13:14**