

bashrc

- description :
- author :
- email : dhan@repia.com
- lastupdate : 2020-01-31

Environment()

```
#
TMOUT=0
export TMOUT
```

export 가

Alias

```
alias rlog='tail -n200 -f ${RSA_ROOT}/logs/javaLog/log_${D_YMD}.txt'
alias tlog='tail -n200 -f ${TOMCAT_ROOT}/logs/localhost.${D_Y-M-D}.log'
alias search='cd ${RSA_ROOT}/bin'
alias sfront='cd ${RSA_ROOT}/bin/html'
```

```
$> source ~/.bashrc
or
$> . ~/.bashrc
```

Example

```
# .bashrc

# User specific aliases and functions

alias rm='rm -i'
alias cp='cp -i'
alias mv='mv -i'
HADOOP_INSTALL=/usr/local/hadoop-1.0.3
PATH=$PATH:$HADOOP_INSTALL/bin

# Source global definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
```

fi

Ref

, [bash](#), [bashrc](#)

From:

<http://125.132.25.164/dokuwiki/> -
2023.12

Permanent link:

<http://125.132.25.164/dokuwiki/doku.php?id=wiki:os:linux:bashrc&rev=1580468638>

Last update: **2022/03/10 19:52**

