

# Sass @import

- description : Sass @import and Partials
- author :
- email : shlim@repia.com
- lastupdate : 2021-04-08

## Ref

[Sass @import and Partials](#)

## Sass Nested Rules

Sass CSS DRY(Don't Repeat Yourself, )  
 DRY( ) 가 .

CSS reset file, , , , Sass .

## Sass Importing Files

CSS 가 Sass @import (directive) .

@import .

CSS "@import" ; 가 HTTP

Sass "@import" CSS ; 가 HTTP

!

## Sass Import Syntax

```
@import filename;
```

### Tip:

가 . Sass .sass .scss 가

CSS 가 .@import (mixins) , (the main file)

가

```
@import "variables";
@import "colors";
@import "reset";
```

: "reset.scss" reset 가 .

### SCSS Syntax (reset.scss)

```
html,
body,
ul,
ol {
  margin: 0;
  padding: 0;
}
```

"reset.scss" "standard.scss"

, 가 : @import 가 ;

### SCSS Syntax (standard.scss):

```
@import "reset";

body {
  font-family: Helvetica, sans-serif;
  font-size: 18px;
  color: red;
}
```

, "standard.css" , CSS .

### CSS output

```
html, body, ul, ol {
  margin: 0;
```

```
padding: 0;
}

body {
  font-family: Helvetica, sans-serif;
  font-size: 18px;
  color: red;
}
```

## Sass Partials

Sass partials are files that end in `.scss`. They are used to organize your CSS into smaller, reusable pieces. A partial is a Sass file that is not meant to be compiled on its own, but is instead included into another Sass file. The syntax for including a partial is `@import "partial.scss";`.

## Sass Partial Syntax

```
_filename;
```

( `"_colors.scss"` partial Sass `"colors.css"` ):

"\_colors.scss":

```
$myPink: #EE82EE;
$myBlue: #4169E1;
$myGreen: #8FBC8F;
```

partial `"_colors.scss"` 가

```
@import "colors";

body {
  font-family: Helvetica, sans-serif;
  font-size: 18px;
}
```

```
colors: $myBlue;
```

„ Sass, @import, and, Partials

From:

<http://125.132.25.164/dokuwiki/> -  
2023.12

Permanent link:

[http://125.132.25.164/dokuwiki/doku.php?id=wiki:sass:sass\\_import&rev=1626865704](http://125.132.25.164/dokuwiki/doku.php?id=wiki:sass:sass_import&rev=1626865704)

Last update: **2022/03/10 19:52**

