

spring_boot_annotation

- description : spring boot annotation
- author :
- email : hylee@repia.com
- lastupdate : 2020-08-21

Annotation

가 .

A

B

C

@ComponentScan

- @Component @Service, @Repository, @Controller, @Configuration Bean
Context bean Annotation
- @Component @Repository, @Service, @Controller
@Repository DAO unchecked exception
DataAccessException 가 . 가

@Configuration

- Configuration @Bean @Autowired
- Spring Batch Job @Configuration .

@ConfigurationProperties

- yaml . default classpath:application.properties .
- (prefix="mail")

mail.host = mailserver@mail.com

```
mail.port = 9000
mail.defaultRecipients[0] = admin> @il.com
mail.port = 9000
mail.defaultRecipients[0] = admin@mail.com
mail.defaultRecipients[1] = customer@mail.com
```

@CookieValue

-
- 가 500
- required가 default true . false null
- public String view(@CookieValue(value="auth")String auth){...}; key가 auth가

@CrossOrigin

- CORS origin AJAX
- @RequestMapping ajax
- @CrossOrigin(origins = "http://jeong-pro.tistory.com", maxAge = 3600)
- http://jeong-pro.tistory.com ajax

@ControllerAdvice

- ControllerAdvice
- @ExceptionHandler(.class)

@Cacheable

- 가
- (=)
-
- @Cacheable(value="cacheKey"), @Cacheable(key="cacheKey")

@CachePut

-
- @Cacheable

@CacheEvict

-
- 가
- () 가
-

@CacheEvict(value="cacheKey"), @CacheEvict(value="cacheKey", allEntries=true)

- allEntries

@CacheConfig

-

D

E

@EnableAutoConfiguration

-
- classpath tomcat-embed-core.jar가
가 setting

@ExceptionHandler(ExceptionClassName.class)

-

@EnableEurekaServer

- Eureka

@EnableDiscoveryClient

- Eureka

F

G

@GetMapping

- @RequestMapping(Method=RequestMethod.GET)
- @PostMapping, @PutMapping, @PatchMapping, @DeleteMapping 가

H

I

@InitBinder

- @Valid 가

J

K

L

@Lazy

-
- @Component @Bean 가 bean

M

@ModelAttribute

- view (VO/DTO) binding
- <input name="id" /> name
set

```
class Person{  
    String id;  
    public void setId(String id){ this.id = id;}  
}
```

N

O

P

| @PostConstruct, @PreConstruct

- `@PostConstruct` / `@PreConstruct` (pre/post)

| @PreDestroy

- `@PreDestroy` (pre)

| @PropertySource

- `@PropertySource` Environment
- `@PropertySource("classpath:/settings.properties")` @Resource Environment

| @PathVariable

- `@PathVariable` URL { }

Q

| @Qualifier("id123")

- `@Autowired` , 가
- (ex) , , ,)
- `@d` , 가
- (ex) , , , ,)

R

| @Required

- `setter`

| @Resource

- `@Autowired` 가 Autowired , Resource

| @RequestMapping

- URL 가 mapping .
-
- @RequestMapping("/list"), @RequestMapping("/home, /about");
- @RequestMapping("/admin", method=RequestMethod.GET)

@ModelAttribute

- Request 가 .

@RequestBody

- (JSON XML) model

@RequestHeader

- Request header 가 .
- @RequestHeader(value="Accept-Language")String acceptLanguage ⇒ ko-KR,ko;q=0.8,en-US;q=0.6

@RequestParam

- @PathVariable . request parameter 가 .

@RequestPart

- Request MultipartFile .
- @RequestPart("file")MultipartFile file .

@ResponseBody

- view가 JSON http response header가 response body .
- return JACKSON .
- context resolver . (viewResolver)

@RestControllerAdvice

- > @ControllerAdvice + @ResponseBody .

@ResponseStatus

- response code reason
- @ResponseStatus(value = HttpStatus.NOT_FOUND, reason = "my page URL changed..") ⇒

@RequiredArgsConstructor

- final , @NonNull .
- (Dependent Injection) .

S

@SpringBootApplication

- @Configuration, @EnableAutoConfiguration, @ComponentScan 3가

@SessionAttributes

-
- @SessionAttributes("name") Model key "name"

@Scheduled

- Linux crontab 가
- @Scheduled(cron = "0 0 07 * * ?") " ()

T

@Transactional

-
- @Transaction(readOnly=true, rollbackFor=Exception.class) : readOnly
rollbackFor Exception
- @Transaction(noRollbackFor=Exception.class) Exception
- @Transaction(timeout = 10) 10

U

V

@Value

- properties 가
- @Value("\${value.from.file}")
- private String valueFromFile; value.from.file 가
- spEL
- @Value("#{systemProperties['priority'] ?: 'some default'}")

@Valid

