How it works	집계가 없으면 작업 만 실행됩니다.	입력을 읽은 다음 비즈니스 로직을 기반으로 처리 한 다음 커밋 간격에 도달 할 때까지 집계하고 마지막으로 데이터 출력 청크를 파일 또는 데이터베이스 테이블에 쓰는 작업이 포함됩니다.
Usage	일반적으로 사용되지 않습니다.	Step을 실행하는 가장 일반적인 방법.
Use Case	일반적으로 리소스를 삭제하거나 쿼리를 실행하는 것과 같은 단일 태스크를 호출하는 시나리오에 사용됩니다.	일반적으로 여러 집계 된 단계를 복사, 처리 및 데이터 전송과 같이 실행해야하는 경우에 사용됩니다

spring-boot-web-application-in-eclipse-itself|How to run Spring Boot web application in Eclipse itself?]]

2. pom.xml Error 표시: Plugin execution not covered by lifecycle configuration

```
In Eclipse Luna 4.4.0, you can chose to ignore this error in preferences
```

Window > Preferences > Maven > Errors/Warnings > Plugin execution not covered by lifecycle configuration. Select Ignore / Warning / Error as you wish. Also, in the quick fix (Ctrl + 1) for this error, it gives an option to mark goal as ignored in Eclipse build in Eclipse preferences (experimental) This is a cleaner way, as it doesn't modify your pom.xml. You will need to do a Maven > Update project to fix the same error in any other project as well.

How to solve “Plugin execution not covered by lifecycle configuration” for Spring Data Maven Builds

From:
http://125.132.25.164/dokuwiki/ - **문제를 잘 정의하는 것은 문제를 절반 해결한 것이다. - 2023.12**

Permanent link:
http://125.132.25.164/dokuwiki/doku.php?id=wiki:springboot&rev=1598533760

Last update: **2022/03/10 19:52**